

4T Motorcycle Oil

Product Description

- **HI-SPEED 4T** : Multigrade SAE 20W-40 four-stroke motorcycle oil exceeding the performance level of API SG and JASO MA. Specifically formulated from selected synthetic base fluids and additives for four-stroke motorcycle and passes Clutch Slip Test on LVFA SAE #2 Friction Machine. Also it has been filed based on the Motorcycle Four Cycle Gasoline Engine Oil Performance Classification (JASO T 903).

Features/Benefits

- Offers good engine cleanliness and provides high control of ring and piston deposit
- Provides excellent lubrication and wear protection of engine and gear
- Enables smooth operation of gear and wet clutches
- Extends engine life
- Passes field performance test in Thailand

Applications

- Recommended for lubricating engine and gearbox of four-stroke motorcycles, such as HONDA , YAMAHA , KAWASAKI and SUZUKI.

Reference Standards

- API SG, JASO MA (JASO Identification No. M066PTT001)

Key Properties

	SAE 20W-40
- Viscosity @ 100 °C, cSt	14.3
- Viscosity Index	114
- Cold-cranking Simulator, @ -15°C, cP	7,380
- Flash Point , (COC) , °C	246
- Pour Point , °C	-18

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.