



# PTT RADIATOR COOLANT

## Coolant

### Product Description

- *PTT RADIATOR COOLANT* : the ethylene glycol base engine coolant, blended with rust and corrosion inhibitor, which is suitable for using in the cooling systems of gasoline and light-duty diesel engines

### Features/Benefits

- Prevents overheating of engine and increasing boiling temperature of water in the radiator
- Provides good rust and corrosion protection of all metals and alloys which are used in the cooling system
- Keep clean in the cooling system
- Compatible with rubber and plastic equipment parts used in the cooling systems

### Applications

- Recommended for cooling systems of gasoline and light-duty diesel engines

#### Suggestion :

1. It is recommended to flush the cooling system by radiator cleaner in the case that radiator is dirty
2. For optimum efficiency, 1 part coolant / 1-3 part water is recommended
3. Recommended 2 years or 40,000 km. draining interval period

### Reference Standards

- ASTM D 3306

### Key Properties

- Specific Gravity@ 15.6 °C (60/60 °F)	1,138
- Boiling Point, undiluted, °C	186
- pH (50 vol % in distilled water)	7.6
- Water, mass %	2.2
- Color	Green

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241  
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.