



AUTOMAT

Automatic Transmission Fluid

Product Description

- **AUTOMAT** : Automatic transmission fluids, exceed performance requirement of General Motors, DEXRON III, blended from high quality mineral base stock and multifunctional additives for using in all types of automatic transmission cars

Features/Benefits

- Improves fuel consumption and provides good seal compatibility
- Gives smoothly start and better speed acceleration
- Provides smoothly and precisely gear change
- Reduces engine wear and extends gear life

Applications

- Recommended for using in all kinds of automatic gear vehicles that required DEXRON III or Ford Mercon Fluid, such as, those of General Motor's, Chrysler's, Ford's, Toyota, Honda, Isuzu, Nissan, Hyundai, Subaru, etc.

Suggestion : No recommend it for electronic transmission control system and continuous variable transmission system (CVT)

Performance Standards

- | | |
|---------------|--------------------|
| - DEXRON III | - FORD MERCON |
| - ALLISON C-4 | - CATERPILLAR TO-2 |

Key Properties

- Viscosity @ 100 °C, cSt	7.7
- Viscosity Index	182
- Flash Point , (COC) , °C	202
- Color	Red
- Pour point, °C	-47
- Copper Strip Corrosion	No. 1

For more information, please contact Fuels & Lubricants Research Department, PTT Research & Technology Institute : Tel. (662) 537-3000 Ext. 2413, 3241
Fax. (662) 537- 3000 Ext. 2236, 3210 or Technical Service Division, Oil Business : Tel. (662) 537-2327-8, (662) 537-2408, (662) 537-2412.